REC'D PCT/PTO 17 DEC 1996

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUM	IBER			
(REV 10-32)					
	Dommond				
TRANSMITTAL LETTER TO THE UNITED STATES	PORTO12				
DESIGNATED/ELECTED OFFICE (DO/EO/US)		ļ			
	PRIORITY DATE CI	LAIMED			
PCT/EP95/01985 26 May 1995	20 June 199	4			
TITLE OF INVENTION: DETECTOR FOR A MEASURING DEVICE					
APPLICANT(S) FOR DO/EO/US					
Helmut Kubisiak					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the follow	ving items under 35 I	J.S.C. 371:			
1.   This express request to immediately begin national examination procedures (3)		•			
2. X The U.S. National Fee (35 U.S.C. 371(c)(1)) and other fees as follows:					
CLAIMS   (1) FOR   (2) NUMBER FILED   (3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS			
TOTAL CLAIMS 19 0	X 22	0 2			
INDEPENDENT 2 = 0	x 80	0			
MULTIPLE DEPENDENT CLAIM(S) (if applicable)	+.				
BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4)):					
For filing with EPO or JPO search report (37CFR 1.492(a)(5))	<b>9</b> 10.00	910.00			
International preliminary examination fee paid to USPTO (37 CFR 1.48	82)				
	\$640.00				
No international preliminary examination fee paid to USPTO (37 CFR					
but international search fee paid to USPTO (37 CFR 1.445(a)(2))	\$710.00				
Neither international preliminary examination fee (37 CFR 1.482) nor					
	s950.00				
International preliminary examination fee paid to USPTO (37 CFR 1.4	82)	•			
	\$90.00	· -			
Surcharge of \$130.00 for furnishing the National fee or oath or					
declaration later than 20 30 months from the earliest		0.00			
claimed priority date (37 CFR 1.492(e)).	,				
TOTAL OF ABOVE CALC	TULATIONS	= 910.00			
Reduction by 1/2 for filing by small entity, if applicable. Affidavit must be	filed also.	455.00			
(Note 37 CFR 1.9, 1.27, 1.28).		455.00			
	SUBTOTAL	+ 455.00			
		100100			
Processing fee of \$130.00 for furnishing the English translation later the	20 30				
months from the earliest claimed priority date (37 CFR 1.492(f)).					
TOTAL NA	TIONAL FEE	\$			
GT CER 1 214W					
Fee for recording the enclosed assignment (37 CFR 1.21(h)).		÷ 40.00			
TOTAL FEES	ENCLOSED	\$495.00			
a X A check in the amount of \$ 495.00 to cover the above fees is enclosed					
b. Please charge my Deposit Account No. in the amount of \$ to cover the above fees.					
A duplicate copy of this sheet is enclosed.					
c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overnayment to Deposit Account No.  A duplicate copy of this sheet is enclosed.					
overnayment to Deposit Account No. A dunicate conv	Of this sheet is end	Hosec.			


_		
	•	ATTOKNEY THAN THE MER
3.		A copy of the International Application as filed (35 U.S.C.371 (c)(2))  a.  is transmitted herewith (required only if not transmitted by the International bureau).  b.  is not required, as the application was filed in the United States receiving Office (RO/US).  c.  has been transmitted by the International Bureau.
4.	Ě	A translation of the International Application into English (35 U.S.C. 371 (c)(2)).
5.		Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).  a.  are transmitted herewith (required only if not transmitted by the International Bureau)  b.  have been transmitted by the International Bureau.
6.		A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
7.	X	An oath or declaration of the inventor (35 U.S.C. 371(c)(4)).
8.		A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).
_		ocument(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
10.		An assignment document for recording.  PLEASE MAIL THE RECORDED ASSIGNMENT DOCUMENT TO:  a.   the person whose signature, name and address appears at the bottom of this page.  b.   the following:
11.		The above checked items are being transmited:  a.  before the eighteenth (18) month publication.  b. after publication and the Article 20 communication but before twenty (20) month form the priority date.  c. after twenty (20) months but before twenty-two (22) months (surcharge and/or processing fee included).  d. after twenty-two (22) months (surcharge and /or processing fee included).  NOTE: Petition to revive (37 CFR 1.137(a) or (b)) is necessary if 35 U.S.C. 371 requirements submitted after 22 months and NO proper demand for International Preliminary Examination was made by 19 months from the earliest claimed priority date.  e.  by thirty (30) months and a proper demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.  f. after thirty (30) months but before thirty-two (32) months and a proper demand for International Preliminary Examinationwas made by the 19th month from the earliest claimed priority date (surcharge and/or processing fee included).  g. after thirty-two (32) months (surcharge and/or processing fee included).  NOTE: Petition to revive (37 CFR 1.137(a) or (b)) is necessary if 35 U.S.C. 371 requirements submitted after 32 months and a proper demand for International Preliminary Examination was made by 19 months from the earliest claimed priority date.
12.		At the time of transmittal, the time limit for amending claims under Article 19:  a.   has expired and no amendments were made.  b.   has not yet expired.
13.		Certain requirements under 35 U.S.C. 371 were previously submitted by the applicant on, namely:

	MARCUS & ASSOCIATES	
RAME	225 Metcalfe Street, Suite 309	
ADDRESS	Ottawa, Ontario, Canada	
	K2P 1P9	
	Marta Thron	18823
SIGNATURE	MARTIN 5 MARCUS	REGISTRATION NUMBER

.

desi.

Applicant or Patentee: Helmut Kubisiak	Attorney's	PORT01
Serial or Palent No.:	Docket No.:	
Filed or Issued:		
For:DETECTOR FOR MEASURING DEVICE		<del></del>
VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL (37 CFR 1.9(I) and 1.27(c)) — SMALL BUSINESS CO		
hereby declare that I am		
<ul> <li>(X) the owner of the small business concern identified below:</li> <li>( ) an official of the small business concern empowered to act on be</li> </ul>	shalf of the concern	Identified
below:  NAME OF CONCERN  BETARAY KUBISIAK GMBH		MAL A
ADDRESS OF CONCERN Neuenburger Strasse 30,	/1 . /	and the
D=75335 Dobel (DE)		MALL
hereby declare that the above identified small business concern qualifies a defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes section 41(a) and (b) of Title 35, United States Code, in that the number of countries of its affiliates, does not exceed 500 persons. For purponumber of employees of the business concern is the average over the previous the persons employed on a full-time, part-time or temporary basis during liscal year, and (2) concerns are affiliates of each other when either, direct controls or has the power to control the other, or a third party or parties control both.	of paying redisced to employees of the ses of this state in the ses of this state in the ses of the each of the pay period for indirectly, on	econcern, econcern, iods of the e concern
hereby declare that rights under contract or law have been conveyed business concern identified above with regard to the invention, entitled _	to and remain with	the small
DETECTOR FOR A MEASURING DEVICE		
Helmut Kubisiak		
described in		
(x) the specification filed herewith ( ) application serial no, filed, issued,		<u> </u>
If the rights held by the above identified small business concern are no concern or organization having rights to the invention is listed below and held by any person, other than the inventor, who could not qualify as a small CFR 1.9(d) or by any concern which would not qualify as a small business coan nonprofit organization under 37 CFR 1.9(e). *NOTE: Separate verified each person, concern or organization having rights to the invention averentities. (37 CFR 1.27)	no rights to the inv all business concer oncern under 37 CF statements are requ	ention are n under 37 R 1.9(d) or ulred from
NAME		
ADDRESS ( ) INDIVIDUAL ( ) SMALL BUSINESS CONCERN ( ) N	ONPROFIT ORGAI	NIZATION
NAME		
ADDRESS( ) INDIVIDUAL ( ) SMALL BUSINESS CONCERN ( ) N	ONPROFIT ORGAL	NIZATION
I acknowledge the duty to file, in this application or patent, notification of in loss of entitlement to small entity status prior to paying, or at the time of fee or any maintenance fee due after the date on which status as a small e (37 CFR 1.28(b))	any change in statu paying, the earliest o	is resulling of the Issue
I hereby declare that all statements made herein of my own knowledge a made on information and belief are believed to be true; and further that the the knowledge that willful faise statements and the like so made are punisfor both, under section 1001 of Title 18 of the United States Code, and the may Jeopardize the validity of the application, any patent issuing thereoverlied statement is directed.	se statements were hable by fine or Imp it such willful false :	made with risonment, statements
NAME OF PERSON SIGNING x Helmut Kubisiak		
TITLE OF PERSON OTHER THAN OWNER X CEO		
ADDRESS OF PERSON SIGNING x Neuenburger Str	aße 30/1	
1 D-75335 Dobel	DATE X 6 DL	100
SIGNATURE X HILMAN 1 Nobel	DATE x 6 11	21476



## Detector for a Measuring Device

## Description:

The invention relates to a detector for a device used to measure radioactive areas, said device having two electrodes between which a voltage is applied, and having also a counter gas between the electrodes.

The measuring of radioactive areas is carried out in particular to determine radioactive thin-film plates, paper chromatograms, electrophoretograms, thin sections of small organisms, DNA plotting strips or contamination. For this purpose, a Geiger-Müller counter or a proportional counter tube is used. These measuring devices are moved slowly over the surface to be measured and the radioactivity measured is recorded, for example, by a rate meter, counter and plotter.

When an area is measured by means of a proportional counter tube, the latter is incrementally advanced along the pathway to be scanned. Another possibility is to use several individual counter tubes arranged one behind the other.

It is further known in the art that radioactive areas on surfaces can be determined with the aid of a wire mesh detector (multiwire detector). In the radioactive zones, the counter gas between the suspended wire meshes, which are insulated from each other, becomes ionized and the location of the radioactive areas in the wire mesh can be displayed on a screen using known electronic methods of measuring radioactivity. The local distribution of the radioactivity in a sample can also be recorded photographically.

It is also known in the art that the distribution of radiation on surfaces can be measured by applying a layer of photographic emulsion which is blackened by the radiation (autoradiography). However, the disadvantage of this method is that, depending on the amount of activity, long exposure times of up to several months have to be tolerated. In the recent past, autoradiography has been further developed. In order to avoid long exposure times, a layer of phosphorus, for example, is used; electrons in this layer of phosphorus become excited and can be converted into an optical image by scanning them with a laser beam.

The disadvantage of this method, however, is that quantitative determination of the local distribution of the radioactivity is unsatisfactory.

When a multiwire detector is used, the spatial resolution of closely adjacent areas of radioactivity is poor, because obliquely incident radiation also triggers ionization of the gas. An attempt is made to eliminate this deficiency by using a multihole collimator between the radioactive surface and the detector. However, this has the disadvantage that the sensitivity of the measuring device is considerably reduced. In addition, it has been discovered that the lack of rigidity and stability of wire meshes used as electrodes can give rise to problems as regards the reproducibility of the measurements.

The purpose of the present invention is to develop the detector to such an extent that the local resolution is further improved. In addition, the purpose is to improve the reproducibility of the measurements.

This goal is accomplished by means of a detector for measuring radioactive areas, said detector having the features described in

Claim 1. Advantageous refinements of the invention are described in the sub-claims.

The detector according to the invention is characterized by the fact that the electrodes are arranged on opposite surfaces of a support. In addition, channels are provided which pierce the electrodes and the support, so that the counter gas is in contact with the electrodes via these channels.

The counter gas fills the individual channels. Thus, each channel acts as both a collimator and a counter tube in which the gas is ionized once radioactivity penetrates the channel, and finally photoexcitation is triggered as a result of the avalanche effect; this can be easily and rapidly detected, for example, by known photographic methods. Via the totality of the channels in the detector according to the invention, an image is obtained of the distribution of the radioactivity over the surface to be measured. In addition, almost 100% detectability of the particles or quanta travelling vertically in relation to the measurement plane is obtained, and deterioration of the local resolution caused by particles or quanta travelling along obliquely oriented paths is prevented.

The detector as such is rigid and robust, thus guaranteeing reproducibility of the measurements.

In accordance with an advantageous further refinement, the electrodes are arranged directly on the support. The latter consists of an electrically non-conductive material. The support may consist wholly or partially of a ceramic material. Other materials, such as Teflon or epoxide, are possible.

The support may also be made of an electrically conducting material. In this case, it is proposed that a layer of insulation be provided between the electrodes and the support. The use of an electrically conductive material may be of interest if this simplifies the formation of the channels.

In accordance with a further refinement of the concept according to the invention, it is proposed that first and second electrical conductors be arranged over the channels. The first conductors extend in a first direction and the second conductors extend in a second direction. The first and second conductors form a gridlike mesh. The individual conductors are electrically insulated from each other. The individual conductors running in both directions in the same plane, which is parallel to the plane of the electrode, act as triggering electrodes for the ionization processes in the individual channels. If an ionization process is triggered in a channel, a voltage is induced at the point of intersection of the two sets of conductors; this voltage can be evaluated in an evaluation unit and can be displayed, for example, on a screen. By means of this refinement, it is possible to dispense with evaluation by photographic means. As a result, the measuring time can be reduced. It is advantageous to keep the diameter of the channels between 0.2 and 0.05 mm.

The spacing between adjacent channels is advantageously kept at  $0.1\ \text{to}\ 1\ \text{mm}\,.$ 

The spacing between the electrodes should preferentially be between 3 to 10 mm. However, this spacing can be adapted to the energy of the particles or quanta to be measured.

Instead of adapting the spacing between the electrodes, it is proposed that the pressure of the counter gas be varied according

to the energy of the particles or quanta to be measured. This has the advantage that, by varying the pressure, it is possible, using a detector, to measure different particles or quanta.

Advantageously, the detector is arranged in a housing, at least one wall of which is transparent to the type of radiation to be measured.

It has been discovered that the counter gas consists advantageously of a mixture of neon, helium and methane. Methane is used here as a quenching gas.

Further advantages and characteristics of the subject of the invention are explained with reference to an embodiment of the invention, as follows:

Figure 1 is a perspective view of a detector,

Figure 2 is a second view of a detector

Figure 3 is a detector mounted in a housing.

The detector 7 comprises two electrodes 1, 2 between which a voltage V is applied. The electrodes 1, 2 are arranged on opposite surfaces 4, 5 of a support 3. Channels pierce the electrodes 1, 2 and the support 3. The counter gas Z is in contact with the electrodes 1, 2 via the channels 6.

The detector 7 possesses a plurality of channels 6. The channels are formed in the two directions X and Y and are equidistantly spaced from each other. Each channel acts as a collimator and a counter tube.

First and second electrical conductors 8, 9, are arranged over the channels 6. The first conductors 8 extend in a first direction, namely the X-direction in the view presented here. The second conductors 9 extend in a second direction (Y-direction). The individual conductors 8 and 9 are electrically insulated from each other.

The points of intersection 8, 9 are positioned over the channels 6. Each individual conductor 8, 9 is connected with an evaluation unit, which is not shown here. The conductors 8 or 9 may be installed in an electrically non-conducting layer. These layers may be applied directly to an electrode. The layers may also be arranged at a distance from the electrode, as still remains to be described.

An ohmic resistore can be provided at each conductor. A constant voltage is applied to each conductor. If ionization occurs in a channel 6, a voltage is induced in the conductors 8, 9 assigned to the channel 6. From the change in voltage in the individual conductors 8, 9, it is possible to determine the location of the event.

The detector may be arranged in a housing 10. The housing 10 possesses a gas inlet 11 and a gas outlet 12. The wall 13 arranged opposite the electrode 1 is provided with an opening 14 corresponding to the electrode 1. By means of a device not shown here, it is possible to position a layer of photographic emulsion over the opening 14.

If a detector is used in a housing, as shown in Fig. 3, the inner chamber formed by the housing and a closure, not shown here, of the opening 14 must be flushed out using a flushing gas. Once the inner chamber has been flushed out, a counter gas is introduced

into the inner chamber. The gas pressure in the inner chamber is measured and held constant by a regulating means, which is not shown here, in order to achieve uniform sensitivity.

Instead of the opening 14, the wall 13 may consist of a material which is transparent to the type of radiation being measured. The housing of the detector may then be hermetically sealed so that no gas losses occur.


## Claims

- 1. A detector for a device for measuring radioactive areas, said device having two electrodes (1; 2), between which a voltage V is applied, and also having a counter gas (Z), characterized in that the electrodes (1;2) are arranged on opposite surfaces (4;5) of a support (3), and further characterized in that channels (6) are provided which pierce the electrodes (1;2) and the support (3), and as a result the counter gas (Z) is in contact with the electrodes (1;2) via the channels (6).
- 2. A detector according to Claim 1, characterized in that the electrodes (1;2) are arranged directly on the support (3), and the support (3) consists of an electrically non-conducting material.
- 3. A detector according to Claim 1, characterized in that an insulating layer is in each case provided between the electrodes (1;2) and the support (3).
- 4. A detector according to Claim 1 or 3, characterized in that the support (3) consists wholly or partially of a ceramic material.
- 5. A detector according to one of the Claims 1 to 4, characterized by a plurality of first and second electric conductors (8;9) arranged over the channels (6), the first conductors (8) extending in a first direction (X) and the second conductors (9) extending in a second direction (Y),

and characterized also in that the conductors (8;9) are connected to an evaluation unit.

- 6. A detector according to one of the Claims 1 to 5, characterized in that the diameter of the channels (6) is between 0.2 and 0.005 mm.
- 7. A detector according to one or more of the Claims 1 to 6, characterized in that the spacing between adjacent channels (6) is 0.1 to 1 mm.
- 8. A detector according to one or more of the Claims 1 to 7, characterized in that the spacing between the electrodes (1;2) is adjusted, preferably in the range from 3 to 10 mm, according to the energy of the particles or quanta to be measured.
- 9. A detector according to one or more of the Claims 1 to 7, characterized in that the pressure of the counter gas can be varied according to the energy of the particles or quanta to be measured.
- 10. A measuring device having a detector according to one or more of the foregoing claims, characterized in that the detector is arranged in a housing (10), at least one wall of which is transparent to the type of radiation to be measured.
- 11. A measuring device with a detector according to one or more of the Claims 1 to 9, characterized in that the counter gas is a mixture of neon, helium and methane.

- 12. A measuring device according to Claim 11, characterized in that the counter gas contains 30-95% neon, 0-65% helium and 3.5% methane.
- 13. A measuring device according to Claim 12, characterized in that the counter gas contains 65.5% neon, 30% helium and 4.5% methane.







Fig. 2



## RULE 63(37 C.F.R.1.63) DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to the name, and I believe I am the original first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

	DETECTOR FOR A MEAN RING DEVI	COLON
the specification of which	MAI	
<pre>(X) is attached hereto. ( ) was filed on</pre>	as U.S. April. Seri	38)
() was filed as PCT Intl. A and if applicable to U.S. or	Appln. No. PCT/ PCT appln.) was amended	
specification, including the acknowledge the duty to disc application in accordance wire under 35U.S.C.119/365 of any listed below and have also ide certificate having a filing d	e claims, as amended by any a lose information which is mate th 37C.F.R.1.56(a). I hereby foreign application(s) for p entified below any foreign appl	erial to the examination of this claim foreign priority benefits extent or inventor's certificate ication for patent or inventor's claimed
Prior Foreign Application(s): Application Number	: Country	Day/Month/Year Filed
P 44 23 338.8	DE	June 20, 1994
provided by the first paragra information as defined in 37C. applications and the national	sted above or below and, insoftion is not disclosed in such uph of 35U.S.C.112, I acknowled F.R.1.56(a) which occurred bet or PCT international filing of	Il prior United States and PCT ar as the subject matter of each prior applications in the manner ge the duty to disclose material ween the filing date of the prior date of this application.
Prior U.S./PCT Application(s) Application Serial No.	): Day/Month/Year Filed	Status: patented, pending, abandoned
PCT/EP95/01985	26/May/1995	pending
statements made on information statements were made with the punishable by fine or imprison States Code and that such application or any patent issues 18823) of Marcus & Associates, telephone number (613)232-268	knowledge that wilful false stomment, or both, under Section wilful false statements may sued thereon. And I hereby apply, P.O. Box 8721, Station "T", Communications as a control of the patent of the patent.	knowledge are true and that all be true; and further that these atements and the like so made are 1001 of Title 18 of the United jeopardize the validity of the point Martin J. Marcus (Reg. No. Ottawa, Ontario, Canada, KIG 3J1, are to be directed), to prosecute and Trademark Office connected
(1) Inventor's Signature	Helmut Mulinian	Date <u>06 DLC 1936</u>
Inventor's Name (typed)	Helmut First Middle	Kubisiak DE Family Name Citizenship
Residence <u>Neuenbürg</u>	ger Strasse 30/1, D-75335 Dobe	L (DE) DEX
Post Office Address Neu	uenbürger Strasse 30/1, D-7533	5 Dobel (DE)